## PRODUCT INFORMATION


# Finishfit® OIL BoPack GAMA FCM

# 2370 I 2371 I 2372

## FIELD OF APPLICATION

Finishfit® OIL BoPack GAMA FCM coatings are universal, oil-based coatings for processing in printing units. They are suitable for absorbent substrates, especially for food contact material (FCM) in indirect contact.

## PROPERTIES

- Supports matt-gloss effects
- Based on renewable raw materials
- Free of mineral oil
- Cobalt-free
- Easy to apply with and without fountain solution
- Fast setting
- Suitable for use on food contact material (FCM) in indirect contact

## VARIANTS

- Finishfit® OIL BoPack GAMA FCM Gloss 2370
- Finishfit® OIL BoPack GAMA FCM Silk Matt 2371
- Finishfit® OIL BoPack GAMA FCM Matt 2372

**Epple Druckfarben AG**
Gutenbergstr. 5 . 86356 Neusäß . Germany . Tel. +49 821 4603 0 . Fax +49 821 4603 200 . info@epple-druckfarben.de
Further information under: **www.epple-druckfarben.de**

## STANDARDS

- The entire manufacturing process as well as the incoming and outgoing goods inspections are subject to the strict requirements of GMP Regulation (EC) No. 2023/2006.
- Suitable for printing on food contact materials according to Regulation (EC) No. 1935/2004

## APPLICATION

- Always read the label and the product information before use
- The properties depend on the substrate and the application quantity
- Stir well before use
- A light use of an IR dryer enables faster further processing
- Not a complete replacement for water-based dispersion coatings

## ADDITIVES

- Cleanfit Roller Paste 2299
- Washfit All AF 2232
- Powderfit Medium 2135 or Powderfit Medium 2136

## STORAGE

- Protect from frost, heat and direct sunlight
- Storage only in original packaging at 10 – 30 °C (50 – 86 °F)
- Unopened and correctly stored, the varnishes have a shelf life of 24 months from delivery date

## STANDARD PACKAGING

- 2.5 kg tin